



## Prensa cabos - visão geral

ÖLFLEX®  
UNITRONIC®  
ETHERLINE®  
HITRONIC®  
EPIC®  
SKINTOP®  
SILVYN®  
FLEXIMARK®  
ACESSÓRIOS  
APÊNDICE

Critérios de utilização	Prensa-cabos																																						
	Página																																						
	712	713	715	720	727	743	745	788	784	718	717	719	790	784	791	724	725	792	785	728	732	733	794	722	722	729	729	730	758	809	756	787	786	735	726	734	737		
																																							
<input checked="" type="checkbox"/> Propriedades																																							
Classe de proteção IP/NEMA	68/69	68	68	68	64	66	68	68	68	68	68	68	68	68	68	**	68	68	68	68	68/69	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68/69		
Rosca de conexão métrica	✓				✓			✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Rosca de conexão PG																																							
Rosca de conexão NPT																																							
Para cabos redondos	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Para cabos planos																																							
Metal	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Plástico	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Ângulo																																							
Alívio de esforço	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Proteção contra vibração	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Proteção anti-torção																																							
Conexão da blindagem																																							
Utilização em áreas perigosas Ex																																							
Livres de halogênio																																							
<input checked="" type="checkbox"/> Aprovações																																							
cULus, cURus, TÜV, VDE, DNV	✓																																						
VDE, cULus, cURus, DNV		✓	✓																																				
VDE			✓																																				
UL, UR, CSA, TÜV																																							
UL, UR, CSA																																							
cULus, cURus, VDE, DNV																																							
cULus, cURus, DNV																																							
VDE, cULus, DNV																																							
DNV, ATEX																																							
cULus, cURus, DNV, ATEX																																							
ATEX, DNV																																							
cULus																																							
EHEDG/ECOLAB																																							✓

Critérios de utilização	Prensa-cabos																																					
	Página																																					
	807	757	808	754	805	753	804	798	755	806	752	803	760	811	761	760	810	750	802	751	800	797	749	796	746	795	746	795	747	747	801	799	768	769				
																																						
<input checked="" type="checkbox"/> Propriedades																																						
Classe de proteção IP/NEMA	68	68	68	68	68	65	65	65	65	65	65	65	65	55	55	55	55	55	55	55	55	55	54	54	54	54	54	54	54	54	54	54	54	54	54	68		
Rosca de conexão métrica	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Rosca de conexão PG																																						
Rosca de conexão NPT																																						
Para cabos redondos	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Para cabos planos																																						
Metal	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Plástico	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Ângulo																																						
Alívio de esforço	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Proteção contra vibração	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Proteção anti-torção																																						
Conexão da blindagem																																						
Utilização em áreas perigosas Ex																																						
Livres de halogênio																																						

\*68/69, NEMA 4x/NEMA 6